# SAFETY DATA SHEET RANUC<sup>®</sup> KOP-COAT Revision Date 04-Nov-2015

Version 1

# 1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product nameRamuc ThinnerProduct code9221000M01

#### **<u>1.2 Relevant identified uses of the substance or mixture and uses advised against</u></u>**

Recommended Use	Paint thinner Pool paint
Restrictions on use	Read label instructions and SDS

### 1.3 Details of the supplier of the safety data sheet

Su	laa	lier

Kop-Coat, Inc. RAMUC 36 Pine Street Rockaway, NJ 07866 1-800-221-4466

#### 1.4 Emergency telephone number

Emergency te	ephone number
--------------	---------------

Chemtrec: +1 703-527-3887 ex-USA Chemtrec: 1-800-424-9300 USA

# 2. Hazards identification

### 2.1 Classification of the substance or mixture

## GHS Classification in accordance with 29 CFR 1910.1200

Acute toxicity - Inhalation (Vapors)	Category 4
Skin corrosion/irritation	Category 2
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 3

#### 2.2 Label elements

Signal Word Danger

### Hazard Statements

Harmful if inhaled Causes skin irritation Suspected of causing cancer Suspected of damaging fertility or the unborn child May cause damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways Flammable liquid and vapor



# **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Use only outdoors or in a well-ventilated area Wash face, hands and any exposed skin thoroughly after handling Do not breathe dust/fume/gas/mist/vapors/spray Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/Bond container and receiving equipment Use explosion-proof electrical/ventilating/lighting/equipment Use only non-sparking tools Take precautionary measures against static discharge

#### **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention If skin irritation occurs: Get medical advice/attention IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower Wash contaminated clothing before reuse IF INHALED: Remove person to fresh air and keep comfortable for breathing IF SWALLOWED: Immediately call a POISON CENTER or doctor Do NOT induce vomiting In case of fire: Use CO2, dry chemical, or foam to extinguish

## **Precautionary Statements - Storage**

Store locked up Store in a well-ventilated place. Keep cool

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

2.3. Other Hazards Hazards not otherwise classified (HNOC) Not Applicable

# 2.4 Other information

Not Applicable

**Unknown Acute Toxicity** 

< 1% of the mixture consists of ingredient(s) of unknown toxicity

# 3. Composition/Information on Ingredients

Substance Not applicable Mixture

Chemical Name	CAS-No	Weight %
Xylene	1330-20-7	80 - 90
Ethylbenzene	100-41-4	10 - 20
Toluene	108-88-3	1 - 5
CUMENE	98-82-8	< 1

The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First aid measures

#### 4.1 Description of first-aid measures

General advice	For further assistance, contact your local Poison Control Center.		
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Call a poison control center or doctor for treatment advice.		
Skin contact	Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Call a poison control center or doctor for treatment advice.		
Inhalation	Move victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a poison control center or doctor for treatment advice.		
Ingestion	Rinse mouth. Do NOT induce vomiting. If a person vomits when lying on his back, place him in the recovery position. Call a physician or poison control center immediately.		
4.2 Most important symptoms and	4.2 Most important symptoms and effects, both acute and delayed		
Symptoms	See Section 2.2, Label Elements and/or Section 11, Toxicological effects.		
4.3 Indication of any immediate medical attention and special treatment needed			
Notes to physician	There is no specific antidote for effects from overexposure to this material. Treat symptomatically.		
E Eiro Eighting Mossuros			

# 5. Fire-Fighting Measures

# 5.1 Extinguishing media

### Suitable extinguishing media

Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray or fog. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

**Unsuitable Extinguishing Media** Water may be unsuitable for extinguishing fires.

### 5.2 Special hazards arising from the substance or mixture

#### Special Hazard

Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapors may travel to areas away from work site before igniting/flashing back to vapor source Thermal decomposition can lead to release of irritating gases and vapors

Hazardous Combustion Products Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

#### **Explosion Data**

Sensitivity to Mechanical Impact Not sensitive. Sensitivity to Static Discharge Yes.

### 5.3 Advice for firefighters

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out. Thoroughly decontaminate all protective equipment after use. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

# 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Refer to protective measures listed in sections 7 and 8. Avoid exceeding of the given occupational exposure limits (see section 8). Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill.

### 6.2 Environmental precautions

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

#### 6.3 Methods and materials for containment and cleaning up

Methods for Containment	Dike far ahead of liquid spill for later disposal. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Ground and bond containers when transferring material. Take precautionary measures against static discharges. Use non-sparking tools and equipment.

## 7. Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling	Ensure adequate ventilation. Ground and bond containers when transferring material. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product. Use according to package label instructions. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. No smoking.	
Hygiene measures	Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.	
7.2 Conditions for safe storage, inc	cluding any incompatibilities	
Storage Conditions	Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in properly labeled containers. Keep away from food, drink and animal feedingstuffs. Store in accordance with local regulations.	
Materials to Avoid	No materials to be especially mentioned.	

## 8. Exposure controls/personal protection

# 8.1 Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWAEV
Xylene	STEL: 150 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>	STEL: 150 ppm	TWA: 434 mg/m <sup>3</sup>	TWA: 434 mg/m <sup>3</sup>	STEL: 150 ppm
				STEL: 150 ppm	STEL: 150 ppm	
				STEL: 651 mg/m <sup>3</sup>	STEL: 651 mg/m <sup>3</sup>	
Ethylbenzene	TWA: 20 ppm	TWA: 100 ppm	TWA: 20 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 20 ppm
100-41-4		TWA: 435 mg/m <sup>3</sup>		TWA: 434 mg/m <sup>3</sup>	TWA: 434 mg/m <sup>3</sup>	
		_		STEL: 125 ppm	STEL: 125 ppm	

				STEL: 543 mg/m <sup>3</sup>	STEL: 543 mg/m <sup>3</sup>	
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm	TWA: 20 ppm Adverse reproductive effect	TWA: 50 ppm TWA: 188 mg/m <sup>3</sup> Skin	TWA: 50 ppm TWA: 188 mg/m <sup>3</sup> Skin	TWA: 20 ppm
CUMENE 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> S*	TWA: 25 ppm STEL: 75 ppm	TWA: 50 ppm TWA: 246 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 246 mg/m <sup>3</sup>	TWA: 50 ppm

## 8.2 Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Where reasonably practicable **Engineering Measures** this should be achieved by the use of local exhaust ventilation and good general extraction. Use adequate ventilation to maintain airborne concentrations at levels below permissible or recommended occupational exposure limits. 8.3 Individual protection measures, such as personal protective equipment Safety glasses with side-shields. If splashes are likely to occur, wear:. Tightly fitting safety **Eye/Face Protection** goggles. Face-shield. Solvent-resistant gloves. Nitrile rubber. Neoprene gloves. Impervious butyl rubber gloves. Skin and body protection Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Wear suitable protective clothing. Remove and wash contaminated clothing before re-use. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved **Respiratory protection** respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations. **Hygiene measures** See section 7 for more information

# 9. Physical and chemical properties

9.1 Information on basic physical a	na chemical properties	
Physical state	Liquid	
Appearance	No information available	
Color	Colorless	
Odor	Hydrocarbon-like	
Odor Threshold	No information available	
Property_	Values	Remarks • Methods
рН		No information available
Melting/freezing point		No information available
Boiling point/boiling range	139 °C / 282 °F	
Flash Point	27 °C / 81 °F	
Evaporation rate		No information available
Flammability (solid, gas)		No information available
Flammability Limits in Air		
upper flammability limit		No information available
lower flammability limit		No information available
Vapor pressure		No information available
Vapor density		No information available
Specific Gravity		No information available
Water solubility		No information available
Solubility in other solvents		No information available
Partition coefficient		No information available
Autoignition temperature		No information available
Decomposition temperature		No information available
Viscosity, kinematic	> < 20 mm2/s	
Viscosity, dynamic		No information available
Explosive properties		No information available
Oxidizing Properties		No information available
9.2 Other information		
Volatile organic compounds (VOC) content	7.25 lb/gal	

## 9.1 Information on basic physical and chemical properties

7.25 lb/gal

# 10. Stability and Reactivity

#### 10.1 Reactivity

Density

No dangerous reaction known under conditions of normal use

#### 10.2 Chemical stability

Stable under recommended storage conditions

## 10.3 Possibility of hazardous reactions

None under normal processing.

#### 10.4 Conditions to Avoid

Keep away from heat, sparks and flames.

#### 10.5 Incompatible Materials

No materials to be especially mentioned.

### 10.6 Hazardous Decomposition Products

None under normal use conditions. Thermal decomposition can lead to release of irritating gases and vapors.

# **11. Toxicological information**

## 11.1 Acute toxicity

## Numerical measures of toxicity: Product Information

## The following values are calculated based on chapter 3.1 of the GHS document

Unknown Acute Toxicity	< 1% of the mixture consists of ingredient(s) of unknown toxicity
Oral LD50	3,491.00 mg/kg
Dermal LD50	5,043.00 mg/kg
LC50 (Vapor)	12.00 mg/l

# Numerical measures of toxicity: Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Xylene 1330-20-7	3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat)4 h
Ethylbenzene 100-41-4	3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat)4 h
Toluene 108-88-3	2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 28.1 mg/L (Rat)4 h
CUMENE 98-82-8	1400 mg/kg (Rat)	= 12300 µL/kg(Rabbit)	8700 ppm (Rat) 4-h

# 11.2 Information on toxicological effects

# Skin corrosion/irritation

Product Information • No information available <u>Component Information</u> • No information available

#### Eye damage/irritation

Product Information

No information available
<u>Component Information</u>

No information available

## Respiratory or skin sensitization

Product Information • No information available <u>Component Information</u> • No information available

#### Germ cell mutagenicity

Product Information • No information available <u>Component Information</u> • No information available

# Carcinogenicity

Product Information

• The table below indicates whether each agency has listed any ingredient as a carcinogen

**Component Information** 

Contains a known or suspected carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylbenzene	-	Group 2B	-	
100-41-4				

CUMENE	-	Group 2B	Reasonably Anticipated	
98-82-8				

# **Reproductive toxicity**

Product Information • No information available <u>Component Information</u>

No information available

# STOT - single exposure

No information available

## STOT - repeated exposure

May cause adverse liver effects

### Other adverse effects

Product Information • No information available <u>Component Information</u> • No information available

### Aspiration hazard

<u>Product Information</u> • Risk of serious damage to the lungs (by aspiration) <u>Component Information</u>

No information available

# **12. Ecological information**

## 12.1 Toxicity

### **Ecotoxicity**

No information available

< 1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Xylene	-	LC50: 96 h Pimephales promelas	EC50: 48 h water flea 3.82 mg/L
1330-20-7		23.53 - 29.97 mg/L static LC50: 96	LC50: 48 h Gammarus lacustris 0.6
		h Cyprinus carpio 780 mg/L	mg/L
		semi-static LC50: 96 h Cyprinus	
		carpio 780 mg/L LC50: 96 h Poecilia	
		reticulata 30.26 - 40.75 mg/L static	
		LC50: 96 h Pimephales promelas	
		13.4 mg/L flow-through LC50: 96 h	
		Oncorhynchus mykiss 2.661 - 4.093	
		mg/L static LC50: 96 h	
		Oncorhynchus mykiss 13.5 - 17.3	
		mg/L LC50: 96 h Lepomis	
		macrochirus 13.1 - 16.5 mg/L	
		flow-through LC50: 96 h Lepomis	
		macrochirus 19 mg/L LC50: 96 h	
		Lepomis macrochirus 7.711 - 9.591	
		mg/L static	
Ethylbenzene	EC50: 72 h Pseudokirchneriella	LC50: 96 h Oncorhynchus mykiss	EC50: 48 h Daphnia magna 1.8 -
100-41-4	subcapitata 4.6 mg/L EC50: 96 h	11.0 - 18.0 mg/L static LC50: 96 h	2.4 mg/L
	Pseudokirchneriella subcapitata 438	Oncorhynchus mykiss 4.2 mg/L	
	mg/L EC50: 72 h	semi-static LC50: 96 h Pimephales	
	Pseudokirchneriella subcapitata 2.6	promelas 7.55 - 11 mg/L	
	- 11.3 mg/L static EC50: 96 h	flow-through LC50: 96 h Lepomis	
	Pseudokirchneriella subcapitata 1.7	macrochirus 32 mg/L static LC50:	
	- 7.6 mg/L static	96 h Pimephales promelas 9.1 -	

		15.6 mg/L static LC50: 96 h Poecilia reticulata 9.6 mg/L static	
Toluene 108-88-3	EC50: 96 h Pseudokirchneriella subcapitata 433 mg/L EC50: 72 h Pseudokirchneriella subcapitata 12.5 mg/L static	LC50: 96 h Pimephales promelas 15.22 - 19.05 mg/L flow-through LC50: 96 h Pimephales promelas 12.6 mg/L static LC50: 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 14.1 - 17.16 mg/L static LC50: 96 h Oncorhynchus mykiss 5.8 mg/L semi-static LC50: 96 h Lepomis macrochirus 11.0 - 15.0 mg/L static LC50: 96 h Oryzias latipes 54 mg/L static LC50: 96 h Poecilia reticulata 28.2 mg/L semi-static LC50: 96 h Poecilia reticulata 50.87 - 70.34 mg/L static	EC50: 48 h Daphnia magna 5.46 - 9.83 mg/L Static EC50: 48 h Daphnia magna 11.5 mg/L
CUMENE 98-82-8	EC50: 72 h Pseudokirchneriella subcapitata 2.6 mg/L	LC50: 96 h Pimephales promelas 6.04 - 6.61 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 4.8 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 2.7 mg/L semi-static LC50: 96 h Poecilia reticulata 5.1 mg/L semi-static	EC50: 48 h Daphnia magna 0.6 mg/L EC50: 48 h Daphnia magna 7.9 - 14.1 mg/L Static

# 12.2 Persistence and degradability

No information available.

#### 12.3 Bioaccumulative potential

Discharge into the environment must be avoided

Chemical Name	log Pow
Xylene 1330-20-7	3.15
Ethylbenzene 100-41-4	3.118
Toluene 108-88-3	2.65
CUMENE 98-82-8	3.55

#### 12.4 Mobility in soil

No information available.

#### 12.5 Other adverse effects

No information available

# **13. Disposal Considerations**

#### 13.1 Waste treatment methods

Disposal should be in accordance with applicable regional, national and local laws and regulations.

# 14. Transport Information

Note	This product may be reclassified as Consumer Commodity, ORM-D, when shipped by ground; packaging quantity limitations apply.
DOT	Quarts and gallons ship as limited quantity.
MEX	no data available

#### IMDG

Proper	shipping	name	

UN1263, Paint related material, 3, III

#### IATA

Proper shipping name

UN1263, Paint related material, 3, III

## **15. Regulatory information**

# 15.1 International Inventories

Complies Complies Complies Complies Complies Complies Complies Complies
Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIOC - New Zealand Inventory of Chemicals

#### 15.2 U.S. Federal Regulations

#### <u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
Xylene 1330-20-7	1.0
Ethylbenzene 100-41-4	0.1
Toluene 108-88-3	1.0

#### 15.3 Pesticide Information

Not applicable

#### 15.4 U.S. State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
Ethylbenzene - 100-41-4	Carcinogen
Toluene - 108-88-3	Developmental Female Reproductive
CUMENE - 98-82-8	Carcinogen

# 16. Other information

NFPA	Health Hazard 2	Flammability 3	Instability 0	Physical and chemical hazards
HMIS_	Health Hazard 2*	Flammability 3	Physical Hazard 0	Personal protection X

## Legend:

ACGIH (American Conference of Governmental Industrial Hygienists) Ceiling (C) DOT (Department of Transportation) EPA (Environmental Protection Agency) IARC (International Agency for Research on Cancer) International Air Transport Association (IATA) International Maritime Dangerous Goods (IMDG) NIOSH (National Institute for Occupational Safety and Health) NTP (National Toxicology Program) OSHA (Occupational Safety and Health Administration of the US Department of Labor) PEL (Permissible Exposure Limit) Reportable Quantity (RQ) Skin designation (S\*) STEL (Short Term Exposure Limit) TLV® (Threshold Limit Value) TWA (time-weighted average)

# **Revision Date**

04-Nov-2015

Revision Note No information available Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**