



Safety Data Sheet

1. Identification

| | |
|------------------------------------|--|
| Product Information. | 902132900 |
| Product Name: | Ramuc Type A - 329 Royal Blue |
| Recommended Use. | Paints |
| Uses advised against. | Read label instructions and SDS |
| Supplier. | Kop-Coat, Inc. / Pettit Marine Paint Marine Group 36 Pine Street Rockaway, NJ 07866 1-800-221-4466 |
| Emergency telephone number. | Chemtrec: +1-800-424-9300 USA Chemtrec: +1 703-527-3887 ex-USA 24 hrs./day, 7 days/week |

2. Hazards Identification

GHS Classification in accordance with 29 CFR 1910.1200
Acute Tox. 4 Inhalation, Flam. Liq. 2, Repr. 2, Skin Irrit. 2, Skin Sens. 1, STOT RE 2

GHS Pictograms



Signal Word
Danger

Unknown Acute Toxicity
26.0% of the mixture consists of ingredient(s) of unknown acute toxicity

HAZARD STATEMENTS

- Highly flammable liquid and vapour.
- Causes skin irritation.
- May cause an allergic skin reaction.
- Harmful if inhaled.
- Suspected of damaging fertility or the unborn child.
- May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements - Prevention.

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/ vapors/spray.
Wash face and hands and any exposed skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response.

If on skin: Wash with plenty of water.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
If exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Specific treatment (If applicable, see label for any additional instructions).
If skin irritation or rash occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use CO₂ dry chemical or foam to extinguish.

Precautionary Statements - Storage.

Store in a well-ventilated place. Keep cool.
Store locked up.

Precautionary Statements - Disposal.

Dispose of contents in accordance with local/regional/national/international regulations.

3. Composition/Information on Ingredients

| <u>Chemical Name</u> | <u>CAS-No.</u> | <u>Wt. %</u> |
|----------------------------|----------------|--------------|
| Xylene | 1330-20-7 | 25-50 |
| Chlorinated Rubber | 68441-58-7 | 10-25 |
| Ethyl Benzene | 100-41-4 | 10-25 |
| Titanium Dioxide | 13463-67-7 | 2.5-10 |
| Parachlorobenzotrifluoride | 98-56-6 | 1.0-2.5 |
| Toluene | 108-88-3 | 1.0-2.5 |

The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid Measures

Description of first-aid measures.

General advice.

Move victim to a safe isolated area. When symptoms persist or in all cases of doubt seek medical advice.
Call a poison control center or doctor for treatment advice.

Inhalation.

Move to fresh air. Apply artificial respiration if victim is not breathing. Call a poison control center or doctor for treatment advice.

Skin contact.

Wash off immediately with soap and plenty of water. Remove all contaminated clothes and shoes. Remove and wash contaminated clothing before re-use. Call a poison control center or doctor for treatment advice.

Eye contact.

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a poison control center or doctor for treatment advice.

Ingestion.

Do not induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. If swallowed, call a poison control center or doctor immediately.

Symptoms.

See Section 2 and Section 11, Toxicological effects for description of potential symptoms.

Notes to physician.

Treat symptomatically.

5. Fire-fighting Measures

Extinguishing media.

Suitable extinguishing media.

Use: Dry powder, Alcohol-resistant foam, Carbon dioxide (CO₂). Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

Extinguishing media which shall not be used for safety reasons.

Water may be unsuitable for extinguishing fires.

Special hazards arising from the substance or mixture.

Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Most vapors are heavier than air. Vapors may spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Air/vapor mixtures may explode when ignited. Containers may explode when heated.

Advice for firefighters.

Evacuate personnel to safe areas. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures.

Personal precautions.

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. All equipment used when handling the product must be grounded. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Wear protective gloves/clothing and eye/face protection. Stop all work that requires a naked flame, stop all vehicles, stop all machines and equipment that may cause sparks or flames. Do not breathe vapors or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8). Thoroughly decontaminate all protective equipment after use.

Advice for emergency responders.

Refer to protective measures listed in sections 7 and 8. Use personal protection recommended in Section 8.

Environmental precautions.

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

Methods and materials for containment and cleaning up.

Methods for Containment.

Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Ground and bond containers when transferring material. Take precautionary measures against static discharges. Use personal protective equipment. Remove all sources of ignition.

Methods for cleaning up.

Prevent further leakage or spillage if safe to do so. Keep away from open flames, hot surfaces and sources of ignition. Keep in suitable and closed containers for disposal. All equipment used when handling the product must be grounded. Keep combustibles (wood, paper, oil, etc) away from spilled material. Ventilate the area. Use personal protective equipment as required. Shut off ignition sources; including electrical equipment and flames. Clean contaminated objects and areas thoroughly while observing environmental regulations. Never return spills in original containers for re-use.

Reference to other sections.

See section 8 for more information.

7. Handling and Storage

Conditions for safe storage, including any incompatibilities.

Advice on safe handling.

Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Use according to package label instructions. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Wash hands before breaks and immediately after handling the product. Ground and bond containers when transferring material. All equipment used when handling the product must be grounded.

Hygiene measures.

Handle in accordance with good industrial hygiene and safety practice for diagnostics. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Storage Conditions.

Keep container closed when not in use. Keep in properly labeled containers. Keep containers tightly closed in a dry, cool and well-ventilated place. Store in accordance with local regulations. Keep from freezing. Keep away from food, drink and animal feedingstuffs. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

| <u>Chemical Name</u> | <u>ACGIH TLV-TWA</u> | <u>ACGIH-TLV STEL</u> | <u>OSHA PEL-TWA</u> | <u>OSHA PEL-CEILING</u> |
|-----------------------------|-----------------------------|------------------------------|----------------------------|--------------------------------|
| Xylene | 100 ppm | 150 ppm | 100 ppm | N.E. |
| Ethyl Benzene | 20 ppm | N.E. | 100 ppm | N.E. |
| Titanium Dioxide | 10 mg/m ³ | N.E. | 15 mg/m ³ | N.E. |
| Toluene | 20 ppm | N.E. | 200 ppm | 300 ppm |

TLV = Threshold Limit Value TWA = Time Weighted Average PEL = Permissible Exposure Limit STEL = Short-Term Exposure Limit N.E. = Not Established

Engineering Measures.

Ensure adequate ventilation, especially in confined areas. Apply technical measures to comply with the occupational exposure limits.

Personal protective equipment.

Eye/Face Protection.

If splashes are likely to occur, wear: Face-shield. Safety glasses with side-shields. Tightly fitting safety goggles.

Skin and body protection.

Use: Long sleeved clothing. Protective shoes or boots. Solvent-resistant gloves. Solvent-resistant apron and boots. Wear impervious gloves and/or clothing if needed to prevent contact with the material. Gloves must be inspected prior to use. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Remove and wash contaminated clothing before re-use.

Respiratory protection.

In case of inadequate ventilation wear respiratory protection. If exposure limits are exceeded or irritation is experienced, respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

9. Physical and chemical properties.

Information on basic physical and chemical properties.

| | |
|--|----------------------------|
| Physical state | Liquid |
| Appearance | No Information |
| Color | Blue |
| Odor | Aromatic |
| Odor Threshold | No Information |
| pH | No Information |
| Melting/freezing point., °C (°F) | No Information |
| Flash Point., °C (°F) | 12 (53.60) |
| Boiling point/boiling range., °C (°F) | 111 - 3,000 (231.8 - 5432) |
| Evaporation rate | No Information Available |
| Explosive properties. | No Information |
| Vapor pressure. | No Information |
| Vapor density. | No Information |
| Specific Gravity. (g/cm ³) | 1.068 |
| Water solubility. | No Information |
| Partition coefficient. | No Information |
| Autoignition temperature., °C | No Information |
| Decomposition Temperature °C. | No Information |
| Viscosity, kinematic. | 21 |

Other information.

| | |
|---|-------|
| Volatile organic compounds (VOC) content. | 573 |
| Density, lb/gal | 8.891 |

10. Stability and Reactivity

Reactivity.

Stable under normal conditions.

Chemical stability.

Stable under recommended storage conditions.

Possibility of hazardous reactions.

None known based on information supplied.

Conditions to Avoid.

Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Keep away from heat and sources of ignition. Do not freeze.

Incompatible Materials.

None known based on information supplied.

Hazardous Decomposition Products.

Thermal decomposition can lead to release of irritating gases and vapours. Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

11. Toxicological Information

Information on toxicological effects.

Acute toxicity.

Product Information

No Information

The following values are calculated based on chapter 3.1 of the GHS document.

| | |
|------------------------------------|---------------|
| ATEmix (oral) | 4,877.6 mg/kg |
| ATEmix (dermal) | 3,673.4 mg/kg |
| ATEmix (inhalation - vapor) | 105.99 mg/l |

Component Information.

| <u>CAS-No.</u> | <u>Chemical Name</u> | <u>LD50 Oral</u> | <u>LD50 Dermal</u> | <u>LC50 Inhalation</u> |
|----------------|----------------------------|------------------|-----------------------|------------------------|
| 1330-20-7 | Xylene | 3500 mg/kg Rat | >4350 mg/kg Rabbit | 29,08 mg/L Rat (Vapor) |
| 100-41-4 | Ethyl Benzene | 3500 mg/kg Rat | 15400 mg/kg Rabbit | 17.4 mg/L Rat (Vapor) |
| 13463-67-7 | Titanium Dioxide | >10000 mg/kg Rat | N.I. | N.I. |
| 98-56-6 | Parachlorobenzotrifluoride | 13000 mg/kg Rat | >240 mg/kg Rabbit | N.I. |
| 108-88-3 | Toluene | 2600 mg/kg Rat | 12000 mg/kg Rabbit | 12,5 mg/L Rat (Vapor) |

N.I. = No Information

Skin corrosion/irritation.

SKIN IRRITANT.

Eye damage/irritation.

No Information

Respiratory or skin sensitization.

No Information

Ingestion.

May be harmful if swallowed.

Germ cell mutagenicity.

No Information

Carcinogenicity.

No Information

| <u>CAS-No.</u> | <u>Chemical Name</u> | <u>IARC</u> | <u>NTP</u> | <u>OSHA</u> |
|----------------|----------------------|---------------|------------|-------------|
| 1330-20-7 | Xylene | IARC Group 3 | - | - |
| 100-41-4 | Ethyl Benzene | IARC Group 2B | - | - |
| 13463-67-7 | Titanium Dioxide | IARC Group 2B | - | - |
| 108-88-3 | Toluene | IARC Group 3 | - | - |

Reproductive toxicity.

No Information

Specific target organ systemic toxicity (single exposure).

No Information

Specific target organ systemic toxicity (repeated exposure).

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard.

No Information

Primary Route(s) of Entry

No Information

12. Ecological Information

Toxicity.

22.23% of the mixture consists of ingredient(s) of unknown aquatic toxicity

Ecotoxicity effects.

| Chemical Name | Toxicity to algae | Toxicity to fish | Toxicity to daphnia and other aquatic invertebrates |
|---------------------------------------|--|--|---|
| Xylene 1330-20-7 | - | LC50 96 h Pimephales promelas 13.4 mg/L, LC50 96 h Oncorhynchus mykiss 2,661 - 4,093 mg/L, LC50 96 h Oncorhynchus mykiss 13.5 - 17.3 mg/L, LC50 96 h Lepomis macrochirus 13.1 - 16.5 mg/L, LC50 96 h Lepomis macrochirus 19 mg/L, LC50 96 h Lepomis macrochirus 7,711 - 9,591 mg/L, LC50 96 h Pimephales promelas 23,53 - 29,97 mg/L, LC50 96 h Cyprinus carpio 780 mg/L, LC50 96 h Cyprinus carpio >780 mg/L, LC50 96 h Poecilia reticulata 30.26 - 40. | EC50 48 h water flea 3.82 mg/L, LC50 48 h Gammarus lacustris 0.6 mg/L |
| Ethyl Benzene 100-41-4 | EC50 72 h Pseudokirchneriella subcapitata 4.6 mg/L, EC50 96 h Pseudokirchneriella subcapitata >438 mg/L, EC50 72 h Pseudokirchneriella subcapitata 2.6 - 11.3 mg/L, EC50 96 h Pseudokirchneriella subcapitata 1.7 - 7.6 mg/L | LC50 96 h Oncorhynchus mykiss 11.0 - 18,0 mg/L, LC50 96 h Oncorhynchus mykiss 4.2 mg/L, LC50 96 h Pimephales promelas 7.55 - 11 mg/L, LC50 96 h Lepomis macrochirus 32 mg/L, LC50 96 h Pimephales promelas 9.1 - 15.6 mg/L, LC50 96 h Poecilia reticulata 9.6 mg/L | EC50 48 h Daphnia magna 1.8 - 2.4 mg/L |
| Parachlorobenzotrifluoride 98-56-6 | - | LC50 96 h Danio rerio 3 mg/L | EC50 48 h Daphnia magna 3.68 mg/L |
| Toluene 108-88-3 | EC50 96 h Pseudokirchneriella subcapitata >433 mg/L, EC50 72 h Pseudokirchneriella subcapitata 12.5 mg/L | LC50 96 h Pimephales promelas 15.22 - 19,05 mg/L, LC50 96 h Pimephales promelas 12.6 mg/L, LC50 96 h Oncorhynchus mykiss 5.89 - 7,81 mg/L, LC50 96 h Oncorhynchus mykiss 14,1 - 17,16 mg/L, LC50 96 h Oncorhynchus mykiss 5,8 mg/L, LC50 96 h Lepomis macrochirus 11,0 - 15,0 mg/L, LC50 96 h Oryzias latipes 54 mg/L, LC50 96 h Poecilia reticulata 28,2 mg/L, LC50 96 h Poecilia reticulata 50,87 - 70,34 mg/L | EC50 48 h Daphnia magna 5.46 - 9.83 mg/L, EC50 48 h Daphnia magna 11.5 mg/L |

Persistence and degradability.

No data are available on the product itself.

Bioaccumulative potential.

Discharge into the environment must be avoided.

Product name.: 902132900 Ramuc Type A - 329 Royal Blue

| <u>CAS-No.</u> | <u>Chemical Name</u> | <u>log POW</u> |
|----------------|----------------------------|----------------|
| 1330-20-7 | Xylene | 2.77 - 3.15 |
| 100-41-4 | Ethyl Benzene | 3.2 |
| 98-56-6 | Parachlorobenzotrifluoride | 3.7 |
| 108-88-3 | Toluene | 2.7 |

Mobility in soil.

No information

Other adverse effects.

No information

13. Disposal Considerations

Waste Disposal Guidance.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

DOT

Shipping Name: Paint
Hazard Class: 3
UN/NA Number: 1263
Packing Group: II

Additional Information: LTD QTY: This product may be reclassified as "limited quantity" per 49 CFR 173.150 (b)(2) and 49 CFR 172 Special Provision 149.

IMDG

-
Proper Shipping Name: Paint
Hazard Class: 3
UN Number: 1263
Packing Group: II

IATA

Proper Shipping Name: UN1263, Paint
Hazard Class: 3
Packing Group: II

15. Regulatory Information

International Inventories:

TSCA Complies
DSL Complies
DSL/NDSL -
EINECS/ELINCS -
ENCS -
IECSC -
KECI -
PICCS -
AICS -
NZIoC -
TCSI

Product name.: 902132900 Ramuc Type A - 329 Royal Blue

| | |
|----------------------|---|
| TSCA | United States Toxic Substances Control Act Section 8(b) Inventory. |
| DSL | Canadian Domestic Substances List. |
| DSL/NDL | Canadian Domestic Substances List/Canadian Non-Domestic Substances List |
| EINECS/ELINCS | European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances. |
| ENCS | Japan Existing and New Chemical Substances. |
| IECSC | China Inventory of Existing Chemical Substances. |
| KECL | Korean Existing and Evaluated Chemical Substances. |
| PICCS | Philippines Inventory of Chemicals and Chemical Substances. |
| AICS | Australian Inventory of Chemical Substances. |
| NZIoC | New Zealand Inventory of Chemicals. |
| TCSI | Taiwan Chemical Substance Inventory |

U.S. Federal Regulations:

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372: .

| <u>Chemical Name</u> | <u>CAS-No.</u> | <u>Weight Percent</u> |
|----------------------|----------------|-----------------------|
| Xylene | 1330-20-7 | 25-50 |
| Ethyl Benzene | 100-41-4 | 10-25 |
| Toluene | 108-88-3 | 1.0-2.5 |

TOXIC SUBSTANCES CONTROL ACT 12(b):

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:.

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------------|----------------|
| Parachlorobenzotrifluoride | 98-56-6 |

CALIFORNIA PROPOSITION 65 CARCINOGENS

WARNING

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:.

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|--|----------------|
| Ethyl Benzene | 100-41-4 |
| Titanium Dioxide | 13463-67-7 |
| Parachlorobenzotrifluoride | 98-56-6 |
| Benzene, (1-methylethyl)- | 98-82-8 |
| Crystalline silica (Quartz) (Respirable) | 14808-60-7 |

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

WARNING

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| Toluene | 108-88-3 |

16. Other Information

Revision Date: 4/24/2020 **Supersedes Date:** New SDS

Reason for revision: No Information

Datasheet produced by: Regulatory Department

HMIS Ratings:

| | | | | | | | |
|----------------|----|----------------------|---|-------------------------|---|-----------------------------|---|
| Health: | 2* | Flammability: | 3 | Physical Hazard: | 0 | Personal Protection: | X |
|----------------|----|----------------------|---|-------------------------|---|-----------------------------|---|

NFPA Ratings:

| | | | | | | | |
|----------------|---|----------------------|---|---------------------|---|---------------------------------|-----|
| Health: | 2 | Flammability: | 3 | Instability: | 0 | Physical & Chemical: | --- |
|----------------|---|----------------------|---|---------------------|---|---------------------------------|-----|

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.