



Epoxy Painting Service - Pool and Spa

Description

Epoxy painting service of pool or spa floor and walls with one coat of epoxy paint.

Services Include

- Removal of main drain grate, lights, inlets, and deck equipment hanging into the pool (ladders, handrails, etc.)
- Proprietary multi step wash, degrease, de-scale and neutralizing washes to prep the surface for painting.
- Surface moisture readiness testing to assure clean dry surface for adequate paint application.
- Installation and removal of normal ground water control pumps, if required, (see below).
- Up to 2-man (two) hours of scraping or rough up sanding of spotted or stained areas.
- Labor and material for 1-coat (one) of epoxy paint applied to all walls and floor of pool or spa.
- Start fresh water fill, (if required and automated, or someone confirmed available to shut off).
- Equipment start-up, review, and 14 point testing, (assuming water level is adequate for priming and circulation start).
- Test and adjust water chemistry, (chemicals sold separately).
- Return trip to start up equipment, (if water level was not high enough to start on initial visit).

Options

Additional work may be required based on the unknown condition of the walls, floor and sub-surfaces not visible or apparent until surface preparation has begun, owner will be notified and necessary repairs will be quoted.

- These services might include; addressing previous failing, chipping, discolored or un-cured paints, delaminating plaster or underlying structural material, (fiberglass, concrete, patch materials, etc.) failure.
- Additional surface preparation and cleaning may be required for adequate surface profile beyond 2-man hours.
- Owner or Property Manager is to specify if OPTIONAL non-slip texturing is needed / requested for stairs, treads, or any other portion of the pool, additional fees may apply.
- Structural repairs, crack filling, or surface preparation; scraping, grinding, sandblasting, etc. beyond 2-man hours.
- Excessive ground water control IE: any ground water entering through other parts of the structure or system.
- Missing or failed waterline or accent tile and grouting.
- Primer or multiple coats of paint may be required for adequate surface profile and coverage.
- Deck power washing removes dirt, grime, mold and mildew, which can lead to slippery surfaces.

Notes

- Fill water is the sole responsibility of the owner. Poolblu will coordinate delivery if trucked in water is selected.
- Moderate ground water control is included with this service through a single existing hydrostatic relief valve only.
- Surface dry time required prior to paint application, generally 3 to 5 days, (weather and temperature dependent).
- Paint cure time required prior to fill, generally 5 to 7 days above 70 degrees, (weather and temperature dependent).
- Curing of epoxy paint requires adequate consistent air circulation and dry environments.
- Owner is responsible for indoor air circulation and VOC's, to prevent fumes from entering occupied building areas.
- Domestic water (hose bib or equivalent) must be on and available to technicians at the time of service.
- Owner must indicate location and placement of discharge water.
- Any permits, (water discharge, etc.) if required, are the responsibility of the owner.

Availability

- Available in all North and Central American markets.