



## Concrete Crack Repair Epoxy Service

### Description

Repair services to fill concrete cracks and or delamination on pool or spa surfaces with 2-part epoxy.

### Services Include

- Draining of pool or spa to expose cracks.
- Cut and chip out cracks to expose solid concrete.
- Chemically treat surface and pressure wash to clean
- Allow area to dry completely.
- Apply 2-part epoxy to surfaces and hand trowel.
- Smooth and sand level to surface.

### Add-On Options

- Additional surface preparation and cleaning activities beyond normal preparation and processing. These services might include addressing previous failing, chipping, discolored or un-cured paints, delaminating plaster or underlying structural material, (fiberglass, concrete, patch materials, etc.) failure.
- Repairs of surface or structure, (delamination, cracks, etc.). may not be visible and apparent prior to removal of failing surface materials and surface preparation.
- Additional delamination repair is priced and performed on a time and material basis as identified.
- Tile replacement, grouting, painting to match existing.
- Replacement of missing or failed waterline or accent tile. Grouting of existing tile lines.

### Notes

- Epoxy filled surfaces must cure completely prior to pool fill.
- Owner is responsible for having fill water available on-site, or notification of intent to truck in water. Poolblu can coordinate timing of water delivery once notified.
- Weather dependency (outdoor pools) – Epoxy application cannot be performed during freezing or rainy weather.

### Availability

- Available in all North and Central American markets.